






Multi-energy metering
(electricity, water, gas, etc.)
LV/MV/HV network
monitoring
Energy quality



ENERIUM[®]

Multi-energy
power monitors

Functions


Simple, intuitive and customizable interface for quick access to the information that you need.

Real-time display

of instantaneous, average, min and max values.

Time/date-stamped recording

of min and max values




Alarms

- 16 programmable alarms on instantaneous, average, min and max values, as well as analogue and on-off inputs (e.g. circuit-breaker status)
- Recording of the last 64 events (values, dates, times, durations)
- Flashing display if there is an alarm

Numéro	Statut	Relais
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		

Graphics for easier data analysis



- Checking of connections, unbalance measurement and display of phase shift

- Monitoring of load factor (display of V, U, I and P)

Indication of connection errors

before operation begins



Validation and navigation keys
via drop-down menus



Local access via **USB cable/**
optical head for:
- programming
- reading the data
- upgrading the firmware



Recording

- Indices, consumption curves ⁽¹⁾ (electricity, water, gas, etc.) and temperature curves ⁽¹⁾
- Critical parameters with triggering according to 3 different modes (date, alarm, on-off input) and possibility of pre/post trigger ⁽²⁾

(1) Load curves. (2) Trend curves.



Preventive maintenance

- Installation operating time
- Operating time of monitored equipment



Quick programming

- Current transformer ratios and communication parameters can be set on the front panel or remotely
- Possibility of protection by password




Customizable screens

- 3 screens with 4 display lines each to organize the information as you wish



Harmonic analysis

- Measurement of THD per phase on U, I and In
- Spectral analysis per phase up to the 50th order on U, I and In



Qualimetry

Stats Freq. 3U, 3U, unbal. U

Stats	Previous week
10s Stats	100% 99.5% 99%
Frequency	81.7%
U1	100%
U2	0.00%
U12	0.00%
U23	0.00%
U31	0.00%
Unbal. U	0.00%

Voltage events 1


28/10/10 14:55:37:802	U1
U2 Loss of Power	0.00U
28/10/10 14:55:37:792	U1
U1 Loss of Power	0.00U
28/10/10 14:55:36:016	U1
U2 1s786ms	0.00U

- Statistical analysis graphs as per EN50160

- Log of the last 1024 events (dips, outages, overvoltages, overcurrents)
Waveform capture (V-U-I-In)

Multiple applications

In addition to the generic functions of power monitors, the ENERIUM range also offers extensive, customizable communication functions.



Choose your power monitor and related software

ENERIUM®, THE TECHNOLOGICAL REFERENCE for everything from basic applications (secondary switchboard, load monitoring) to the most demanding tasks (metering station).



	ELECTRICAL ENERGY			MULTI-ENERGY		QUALIMETRY
Functional specifications						
Accuracy class (IEC61557-12)	1	0.5	0.5	0.5	0.5 ou 0.2	0.2
Format	96 x 96 mm	96 x 96 mm	96 x 96 mm	144 x 144 mm	144 x 144 mm	144 x 144 mm
Graphic LCD screen	•	•	•	•	•	•
Version without display	—	—	—	—	—	—
Mounting						
	Flush-mounted, DIN rail* or plate-mounted*	Flush-mounted, DIN rail* or plate-mounted*	Flush-mounted, DIN rail* or plate-mounted*	Flush-mounted, DIN rail* or plate-mounted* (Enerium 110)	Flush-mounted, DIN rail* or plate-mounted* (Enerium 210)	Flush-mounted, DIN rail* or plate-mounted* (Enerium 310)
Harmonics						
Max. order	—	25	50	25	50	50
Recording functions						
8 load curves	—	•	•	—	•	•
4 trend curves	—	—	•	•	•	1
Alarms						
Number of alarms	2	16	16	16	16	16
Time/date-stamped events recorded	—	64	64	64	64	64
Qualimetry functions						
Qualimetry according to EN50160	—	—	—	—	—	•
V, I, U and In waveform capture	—	—	—	—	—	16
Storage of last 1024 events (dips, outages, overvoltages) with time/date-stamping	—	—	—	—	—	•
Inputs / outputs						
Max. number	1	2	2	8	8	8
Inputs (optional)						
On-off (pulses or alarm)	—	0,1 or 2	0,1 ou 2	0, 2, 4, 6 or 8	0, 2, 4, 6 or 8	0, 2, 4, 6 or 8
Analogue	—	—	—	—	—	—
Outputs (optional)						
On-off (pulses or alarm)	1	0,1 or 2	0,1 or 2	0, 2, 4, 6, or 8	0, 2, 4, 6, or 8	0, 2, 4, 6, or 8
Analogue	0	0 or 2	0 or 2	0,2 or 4	0,2 or 4	0,2 or 4
Graphics						
Fresnel	—	—	•	•	•	•
Gauges	•	—	—	—	—	—
Histograms of harmonic orders	—	—	•	—	•	•
Communication interface						
Optical / USB	—	Front	Front	Front or rear	Front or rear	Front or rear
Ethernet or RS485	RS485	•	•	•	•	•
Metrological LED	—	—	—	•	•	•
Other functions						
Programming on front panel	•	•	•	•	•	•
Programming via software	—	•	•	•	•	•


* With mounting kit

Advantages



An optical head/USB connection for:

- Programming
- Reading the data
- Upgrading the software



Display with graphics (Fresnel, gauges, harmonics)




Screenless version for DIN-rail or plate mounting (ENERIUM 110/210/310)



Up to 8 on-off or analogue inputs/outputs

.view



Architecture:

- Display of the electrical installation's architecture



Display:

- All the quantities managed by the power monitor
- Reading of 1 s, average, min and max values with time/date-stamping



Summary tables:

- Simplified analysis of the results
- Alarms log
- Statistics compliant with EN50160
- Time/date-stamped events (dips, outages, overvoltages, etc.)




Data export:

- Alarms log
- EN50160 statistics
- Voltage events (dips, outages, overvoltages, etc.)
- Waveforms
- Multiple export formats: .csv, .xls, .txt, etc.

.view +


Energy management:

- Display of load curves
- Comparison of energy consumption with temperature curves




Installation monitoring:

- Recording of critical parameters
- Analysis of recordings after triggering by alarm




Harmonic analysis:

- Simplified analysis of the results by means of graphics



Phase shift measurement:

- Implementation made easier by simple visual check
- Measurement of phase angles and unbalance (V, U, I)



Related software

Functions	E.set ^{(1) (2)}	E.view ⁽²⁾	E.view + ⁽²⁾
Creation of network architecture	•	•	•
Configuration (remote or local)	•	•	•
Data display and export	•	•	•
Graphics	•	•	•

(1) delivered as standard with each instrument

(2) Except on Enerium 30

Functions


Measurements

	1S	min	max	average	min average	max average
V, U	●	○	●	●		○
Vearth	○	○	○	○		○
I	●	○	●	●		○
In (calculated or measured) ⁽¹⁾	●	○	●	●	○	○
P (4 quadrants)	●		○	○		
Pt (4 quadrants)	●	●	○	●		○
Q (4 quadrants)	●		○	○		
Qt (4 quadrants)	●	○	○	●		○
S	●		○	○		
St	●	●	●	○		○
FP (4 quadrants)	●			○		
Fpt (4 quadrants)	●			●	○	○
Cosp (4 quadrants)	○			○		
Cospt (4 quadrants)	○	○	○	○	○	○
Tanpt (4 quadrants)	●			●	○	○
Frequency	●	○	●	○		
V crest factor	○			○		○
I crest factor	○			○		○
U unbalance	○			○		○
Harmonics on V, U, I	○					
Harmonics on In	○					
THD V, U, I	●			●		○
THD In	●		○	●		○
Active energy (receiver, generator)	●					
Reactive energy (Qcad1, 2, 3, 4)	●					
Apparent energy (receiver, generator)	●					
On-off input (pulse mode)	○					
Analogue input (Enerium 100/200)	○	○	○	○	○	○
Voltage presence hour meter (U)	○					
Load hour meter (I)	●					
Auxiliary power supply hour meter	●					


○ Except on 30
⁽¹⁾ on Enerium 30/50/150, calculated only

Connection diagrams


Single-phase




Balanced 3-phase, 4 wires - 1 CT
 Except on Enerium 30




Balanced 3-phase, 4 wires - 1 CT
 Enerium 30 only




Balanced 3-phase, 3 wires - 1 CT
 Enerium 30 only




Unbalanced 3-phase, 4 wires - 3 CTs




Unbalanced 3-phase, 4 wires - 4 CTs
 Except on Enerium 30/50/150




Unbalanced 3-phase, 3 wires - 3 CTs



Unbalanced 3-phase, 3 wires - 2 CTs



Example of connection to VT



Trend curves

(except on Enerium 30/50)

1S VALUES	
V, Vearth	●
U12, U23, U31	●
I1, I2, I3, In	●
Pt	●
Qt	●
St	●
PFt	●
U unbalance	●
THD V, U, I, In	●
Analogue inputs (Enerium 100/200 only)	●
AVERAGE VALUES	
V1, V2, V3	●
U12, U23, U31	●
I1, I2, I3, In	●
Gen: P1, P2, P3, Pt	●
Rec: P1, P2, P3, Pt	●
Analogue inputs (Enerium 100/200 only)	●
Gen: PF1, PF2, PF3, PFt	●
Rec: PF1, PF2, PF3, PFt	●
Gen: Cosp1, Cosp2, Cosp3, Cospt	●
Rec: Cosp1, Cosp2, Cosp3, Cospt	●
Tanpt	●
Frequency	●
Crest factor V1, V2, V3	●
Crest factor I1, I2, I3	●
THD U12, U23, U31	●
THD I1, I2, I3, Ineutral	●
THD V1, V2, V3	●

Load curves

(except on Enerium 30/100 and 110)

AVERAGE VALUES	
Pt Gen, Pt Rec	●
Qcad1, Qcad2, Qcad3, Qcad4	●
St Gen, St Rec	●
On-off inputs	●
Analogue inputs (Enerium 200 only)	●


Accessories

Kit for DIN-rail or plate mounting



Dimensions


ENERIUM 30/50/150



ENERIUM 100/200/300



ENERIUM 110/210/310



Alarms

1S VALUES	
V1, V2, V3	●
Vearth	○
U12, U23, U31	●
I1, I2, I3, In	●
Pt	●
Qt	●
St	●
PFt	●
Cosp1	○
Tanpt	●
Frequency	●
U unbalance	○
THD V, U, I, In	○
3 hour meters: network presence, on-load presence, aux. source	○
Analogue inputs (Enerium 100/200 only)	○
AVERAGE VALUES	
Pt Gen, Pt Rec	○
Qt Gen, Qt Rec	○
St	○
Tanpt (except on Enerium 30/50/150)	○
Analogue inputs (Enerium 100/200 only)	○
ON-OFF INPUTS (Enerium 100/200 only)	
○ Except Enerium 30	

Analogue outputs (option)

(Except Enerium 30)

1S VALUES	
V1, V2, V3, Vearth	●
U12, U23, U31	●
I1, I2, I3, In	●
Pt	●
Q1, Q2, Q3	●
Qt	●
S1, S2, S3	●
St	●
PF1, PF2, PF3	●
PFt	●
Cosp1, Cosp2, Cosp3	●
Cosp1	●
Tanpt	●
Frequency	●

Specifications

	ENERIUM 30 Class 1	ENERIUM 50/150 Class 0.5 s	ENERIUM 100/200 Class 0.5 s	ENERIUM 200 Class 0.2 s	ENERIUM 300 Class 0.2 s
Electrical network					
Max. phase-to-phase voltage measured	650 kV				
VT ratio	VT primary: 100 V to 650 kV VT secondary: 100 V to 480 V				
Max. current measured	25,000 A				
CT ratio	CT primary: 1 A to 25,000 A CT secondary: 1 A or 5 A				
Max. power measured	2 GW				
Voltage inputs (AC)					
Measurement range	5 to 130 % of Vn for Vn = 57.7 / 230 V (ph-N) 5 to 130 % of Un for Un = 100 / 400 V (ph-ph)				
Crest factor	2				
Measurement accuracy (U and V)	0.5 % from 20 % to 130 % of Un / Vn	0.2 % from 20 % to 130 % of Un/Vn			
Overvoltage	Transient U = 800 V for 24 hours Permanent 130 % of 400 V = 520 V				
Frequency	50 / 60 Hz	50 / 60 Hz or 400 Hz	50 / 60 Hz	50 / 60 Hz or 400 Hz	50 / 60 Hz
Consumption	< 0.1 VA	< 0.15 VA	< 0.1 VA		
Input impedance	0.45 MΩ	0.44 MΩ	1 MΩ		
Current inputs (AC)					
Measurement range	1 % to 130 % of In for In = 5 A				
Crest factor	3				
Measurement accuracy	0.5 % from ≥ 10 % to ≤ 130 %	0.2 % from ≥ 10 % to ≤ 130 % 0.5 % from ≥ 5 % to ≤ 10 % 1 % from ≥ 1 % to ≤ 5 %			
Acceptable overload	Transient I = 250 A for 1 second Permanent 130 % of 5 A = 6.5 A				
Consumption	< 0.15 VA				
Compliance with standards					
EN62053-22	Active energy Class 1 Reactive energy Class 2	Active energy Class 0.5 s		Active energy Class 0.2 s	Active energy Class 0.2 s
		Active energy Class 0.5 s			
IEC61557-12 PMD SD/SS	V,I Class 0.5 P,S Class 0.5	V,I Class 0.2 P,S Class 0.5	class 0.5	class 0.2	class 0.2
		Active energy Class 0.5 Reactive energy Class 0.5		Active energy Class 0.2 Reactive energy Class 0.5	Active energy Class 0.2 Reactive energy Class 0.2
Multi-measurement (accuracies)					
Active power and energy	1 % for 5 % In ≤ I ≤ Imax	0.5 % for 5 % In ≤ I ≤ Imax		0.2 % for 5 % In ≤ I ≤ Imax	
Reactive power and energy	2 % for 5 % In ≤ I ≤ Imax	0.5 % for 5 % In ≤ I ≤ Imax			
Apparent power and energy	1 % for 5 % In ≤ I ≤ Imax	0.5 % for 5 % In ≤ I ≤ Imax			
Power factor (PF) and cosφ	± 0.05 counts when 0.5 inductive < PF < 0.5 ± 0.1 counts when 0.2 inductive < PF < 0.2 capacitive	± 0.02 counts when 0.5 inductive < PF < 0.5 capacitive ± 0.05 counts when 0.2 inductive < PF < 0.2 capacitive			
Frequency	± 0.1% from 42.5 to 69 Hz				
Sampling frequency	6.4 kHz to 50 Hz				
THD-I, THD-V and THD-U	± 0.5 counts				
Harmonics order by order	–	± 0.5 counts			

	ENERIUM 30 Class 1	ENERIUM 50/150 Class 0.5 s	ENERIUM 100/200 Class 0.5 s	ENERIUM 200 Class 0.2 s	ENERIUM 300 Class 0.2 s
RS485 output					
Connection	2 wires, half duplex				
Protocol	ModBus / JBus RTU mode				
Speed (configurable)	2,400 - 4,800 - 9,600 - 19,200 - 34,800 (115,200 on ENERIUM 50/150)				
Parity	Even, odd or none				
JBus addresses	1 to 247				
Ethernet output					
Type	-	RJ45 - 8 pins			
Protocol	-	ModBus/TCP			
Speed (configurable)	-	Compatible with 10, 100 and 1,000 base T			
Auxiliary power supply					
Power supply	230...400 Vac ± 20 % (< 10 VA)	80 to 265 Vac (< 15 VA) 42.5 to 69 Hz 110 to 375 Vdc 19 to 57 Vdc (< 7.5 W)	80 to 265 Vac (< 20 VA) - 42.5 to 69 Hz 110 to 375 Vdc 19 to 57 Vdc (< 10 W)		
Digital inputs (on-off or metering pulse)					
Operating voltage	-	Up to 70 Vdc max.	High level: 10 to 70 Vdc Low level: 0 to 5 Vac		
Min. signal width	-	High level: 30 ms Low level: 30 ms			
Consumption	-	< 0.5 W			
Pulse or alarm relay outputs					
Type	Static relay				
Operating voltage	70 Vdc max 33 Vac max	24 to 110 Vdc ± 20 % 24 to 230 Vac ± 10%			
Max. current	100 mA	100 mA			
Compliance with standard	IEC 62053-31				
Analogue inputs					
Scale	-	-	Configurable between -20 to +20 mA		
Power consumption	-	-	< 50 mW		
Input impedance	-	-	50 Ω		
Analogue outputs					
Scale	-	Configurable between -20 to + 20 mA			
Acceptable overload	-	500 Ω			
Response time	-	< 500 ms			
Storage					
Non-volatile memory	Configuration parameters – Recordings (curves, alarms, min-max, qualimetry events log, IEC 50160 statistics)				
RAM	Capture of waveforms				
Environmental specifications					
Operating temperature	- 10 °C to + 55 °C (K55 according to IEC61557-12)				
Operating humidity	95 % to 40 °C				
Storage temperature	- 25 °C to + 70 °C				
Safety specifications					
Pollution	2				
Behaviour in fire	UL 94, severity V1				
Installation category	3				

To order

Standard ENERIUM

Model	Frequency	Accuracy class	Power supply	Communication	On-off inputs	On-off outputs	Analogue outputs	Reference
ENERIUM 30	50 / 60 HZ	1	230 to 400 Vac/Vdc	-	0	0	0	P01330821
ENERIUM 30	50 / 60 HZ	1	230 to 400 Vac/Vdc	-	0	1	0	P01330822
ENERIUM 30	50 / 60 HZ	1	230 to 400 Vac/Vdc	RS485	0	0	0	P01330823
ENERIUM 30	50 / 60 HZ	1	230 to 400 Vac/Vdc	RS485	0	1	0	P01330824
ENERIUM 50	50 / 60 HZ	0.5 s	80 to 265 Vac / 110 to 375 Vdc	RS485	0	0	0	P01330805
ENERIUM 50	50 / 60 HZ	0.5 s	80 to 265 Vac / 110 to 375 Vdc	Ethernet	0	0	0	P01330806
ENERIUM 50	50 / 60 HZ	0.5 s	80 to 265 Vac / 110 to 375 Vdc	RS485	1	1	0	P01330807
ENERIUM 50	50 / 60 HZ	0.5 s	80 to 265 Vac / 110 to 375 Vdc	Ethernet	1	1	0	P01330808
ENERIUM 150	50 / 60 HZ	0.5 s	80 to 265 Vac / 110 to 375 Vdc	RS485	0	0	0	P01330809
ENERIUM 150	50 / 60 HZ	0.5 s	80 to 265 Vac / 110 to 375 Vdc	Ethernet	0	0	0	P01330810
ENERIUM 150	50 / 60 HZ	0.5 s	80 to 265 Vac / 110 to 375 Vdc	RS485	0	2	0	P01330811
ENERIUM 150	50 / 60 HZ	0.5 s	80 to 265 Vac / 110 to 375 Vdc	Ethernet	0	2	0	P01330812
ENERIUM 100	50 / 60 HZ	0.5 s	80 to 265 Vac / 110 to 375 Vdc	RS485	0	0	0	P01330831
ENERIUM 100	50 / 60 HZ	0.5 s	80 to 265 Vac / 110 to 375 Vdc	RS485	2	2	0	P01330832
ENERIUM 200	50 / 60 HZ	0.5 s	80 to 265 Vac / 110 to 375 Vdc	RS485	4	2	0	P01330833
ENERIUM 200	50 / 60 HZ	0.5 s	80 to 265 Vac / 110 to 375 Vdc	Ethernet	2	2	2	P01330834
ENERIUM 210	50 / 60 HZ	0.5 s	80 to 265 Vac / 110 to 375 Vdc	Ethernet	8	0	0	P01330835

Configured products

ENERIUM

1	2	3	4	5	6	7	8	9
---	---	---	---	---	---	---	---	---

1 Model

50	ENERIUM 50 – Electrical energy – Load curves - Format 96 x 96
150	ENERIUM 50 + Trend curves - Format 96 x 96
100	ENERIUM 100 – Multi-energy - Trend curves - Format 144x144
110	ENERIUM 100 screenless version - Format 144x144
200	ENERIUM 100 + Load curves - Format 144x144
210	ENERIUM 200 screenless version - Format 144x144
300	ENERIUM 200 + Qualimetry
310	ENERIUM 300 screenless version

2 Frequency of network measured

0	50 / 60 Hz
1	400 Hz (except on Enerium 100 / 200 class 0.5s / 300)

3 Auxiliary power supply

0	80 to 265 Vac / 110 to 375 Vdc
1	19.2 to 58 Vdc

4 Communication

0	RS485
1	Ethernet

Note : with choices 5, 6, 7 and 8, it is possible to have a maximum of 8 inputs and/or outputs (ENERIUM 100-110/200-210).

Note: for the Enerium 50/150, choices 5 and 6 only allow the following combinations: 0-0, 1-1, 2-0, 0-2.

5 Metering (or On-Off) inputs

0	none
1	1 input (only on ENERIUM 50/150)
2	2 inputs
4	4 inputs (except on ENERIUM 50/150)
6	6 inputs (except on ENERIUM 50/150)
8	8 inputs (except on ENERIUM 50/150)

6 On-Off outputs

0	none
1	input (only on ENERIUM 50/150)
2	2 inputs
4	4 inputs (except on ENERIUM 50/150)
6	6 inputs (except on ENERIUM 50/150)
8	8 inputs (except on ENERIUM 50/150)

7 Analogue inputs (ENERIUM 100/200 only)

0	none
2	2 analogue inputs
4	4 analogue inputs
6	6 analogue inputs
8	8 analogue inputs

8 Analogue outputs

0	none
2	2 outputs
4	4 outputs (except on ENERIUM 50/150)

9 Accuracy class

5	0.5 s (except on ENERIUM 300)
2	0.2s (ENERIUM 200/210/300/310 only)

Example : Enerium 200, frequency 50/60 Hz, 80 to 264 Vac auxiliary power supply, RS485 communication, 2 on-off inputs, no on-off outputs, no analogue inputs, no analogue outputs, Class 0.2s

=> order ENERIUM 200 01020002 • 1-200 • 2-0 • 3-1 • 4-0 • 5-2 • 6-0 • 7-0 • 8-0 • 9-2

Logiciels

E.set	P01330501
E.View	P01330601
E.View+	P01330610

Accessories

Optical head for ENERIUM 50/150	P01330403
Optical head for ENERIUM 100/110 - 200/210 – 300/310	P01330401
DIN-rail mounting kit for ENERIUM 30/50/150	P01330830
DIN-rail mounting kit for ENERIUM 100/200/300	P01330360
690 V / 400 V resistive voltage adapter (for wind-turbine applications)	P01330402
Power supply for On-Off inputs 85 to 256 Vac/12 Vdc – 3.5 A (42 W)	ACCJ1004

FRANCE

Enerdis

16, rue Georges Besse – Silic 44
92182 ANTONY Cedex
Tél : +33 1 75 60 10 30
Fax : +33 1 46 66 62 54
info@enerdis.fr
www.enerdis.fr

UNITED KINGDOM

Chauvin Arnoux Ltd

Unit 1 Nelson Ct, Flagship Sq, Shaw Cross Business Pk
Dewsbury, West Yorkshire – WF12 7TH
Tel: +44 1924 460 494
Fax: +44 1924 455 328
info@chauvin-arnoux.co.uk
www.chauvin-arnoux.com

MIDDLE EAST

Chauvin Arnoux Middle East

P.O. BOX 60-154
1241 2020 JAL EL DIB – LEBANON
Tel: +961 1 890 425
Fax: +961 1 890 424
camie@chauvin-arnoux.com
www.chauvin-arnoux.com



**CHAUVIN
ARNOUX**
GROUP